

АВТОБЕТОНОСМЕСИТЕЛЬ НА ЧЕТЫРЁХОСНОМ ШАССИ

XCMG NXG5310GJBN5-12 G5

NXG5310GJBN5 HANVAN G5 LHD MIXER TRUCK TECHNICAL

СПЕЦИФИКАЦИЯ



UNIVERSAL MACHINERY LLC

XUZHOU XCMG AUTO MANUFACTURING CO., LTD

Основные параметры

| | Vehicle Model | | NXG5310GJBN5 |
|--------------------------|---|---------------|-------------------------|
| 设计质量参数 Mass parameter | 整备质量/GVW | | 41000 |
| | 整备轴荷 Kerb axle load | 前轴/Front axle | 6140kg |
| | | 后轴/Rear axle | 7860kg |
| | 最大允许总质量/GCW | | 14100kg |
| | 最大允许轴荷 Max axle load | 前轴/Front axle | 12570kg |
| | | 后轴/Rear axle | 30230kg |
| 性能参数 Performance | 最高车速/Max Speed | | 70km/h |
| | 最小转弯直径/Min. turning diameter | | 20m |
| | 最大爬坡度(≥)/Grade ability(≥) | | 30% |
| | 最大驻坡度(≥)/Hill-hold ability(≥) | | 30% |
| | 百公里油耗/Fuel Consumption | | / |
| | 油箱容积/Fuel tank | | 260L |
| 尺寸参数 Dimensions | 外形尺寸 Overall dimensions | 长/Length | 10005mm |
| | | 宽/Width | 2550mm |
| | | 高/Height | 3850mm |
| | 轴距/Wheelbase | | 1950+2900+1350mm |
| | 轮距 Wheel track | 前轮/Front tire | 2064mm |
| | | 后轮/Rear tire | 1860mm |
| | 最小离地间隙/Min. Clearance | | 250mm |
| | 接近角/Approach angle | | 20° |
| | 离去角/Departure angle | | 18° |
| | 前悬/Front overhang | | 1485mm |
| | 后悬/Rear overhang | | 2365mm |
| | 货厢尺寸/Cargo size | | 12 立方米/12m ³ |
| | 重心高度(空载/满载)/Height of center of gravity (no load / full load) | | 12,271,880 |
| 驾驶室 | 型号/Model | | G5LM |

| | | | |
|---------------------|--------------------------------------|----------------------------------|--|
| Cab | 乘员人数/Passengers | | 2 |
| 发动机 Engine | 型号/Model | | WP10.350E53 |
| | 总排量/Displacement | | 9.726L |
| | 额定功率/Output power | | 257/1900 kW/(r/min) |
| | 最大扭矩/Mix torque speed | | 1600 (1200-1500) N·m/(r/min) |
| 离合器 Clutch | 型号/Model | | Φ430 |
| | 操纵方式/Operation | | 液压操纵气助力/Hydraulic manual |
| 变速器 Transmission | 型号/Model | | 10JSD160T |
| | 操纵方式/Operation | | 软轴/Flexible shaft |
| | 前进档速比/Forward ratio | | 14.86-1.00 |
| | 倒档速比/Reverse ratio | | 14.24/3.19 |
| 驱动桥 Driven axle | 型号/Model | | 13T |
| | 主减速器速比/Ratio | | 4.8 |
| | 制动器类型/Brake type | | 鼓式/Drum type |
| | 差速锁/Differential lock | | 轴间、轮间差速锁 Differential lock between axles and wheels |
| 前轴 Front axle | 型号/Capacity | | 6.5T |
| | 制动器类型/Brake type | | 鼓式 Drum type |
| 车轮 Wheel | 轮辋/Rim | | 8.50V-20 |
| | 轮胎/Tire | | 12.00R20 18PR |
| 车架 Frame | 型式/Type | | 865 |
| | 主纵梁截面/Main beam | | 300×90×8mm |
| | 衬梁截面/Auxiliary beam | | 284×80×5mm |
| | 车架总成宽度 Width of chassis structure | | 865mm |
| 悬架 Suspension | 前/Front | 型式/Type | 纵置多片簧/Multi-spring |
| | | 钢板弹簧片数 Amount of spring plate | 3/3 |
| | 后/Rear | 型式/Type | 纵置多片簧/Multi-spring |
| | | 钢板弹簧片数 Amount of spring plate | 4 |
| 转向系 Steering | 转向器型式/型号/Steering type | | Φ120 循环球式液压助力 Circulating ball type hydraulic power |
| | 转向器速比/Ratio | | 23.27 |

MIXER TRUCK TECHNICAL SPECIFICATION

| | | |
|---------------------------|---|---|
| | 转向油泵最大压力/Max pressure of pump | 15MPa |
| 制动系 Brake | 额定工作压力/Rated working pressure | 1MPa |
| | 行车制动系型式/Driving brake | 双回路气压制动 Dual circuit pneumatic brake |
| | 驻车制动系型式/Parking brake | 弹簧储能断气制动 Spring energy storage air brake |
| | 辅助制动系型式/Assistant brake | 发动机排气制动/Engine exhaust brake |
| 电气系 Electric System | 电压/Voltage | 24V |
| | 发电机功率/Generator power | 2.2kw |
| | 蓄电池电压/电容 Battery voltage and Capacitance | 2×12/165V/Ah |

Vehicle appearance



Vehicle interiors





ООО «Юниверсал Машинери»
г. Киев, Бульвар Верховного Совета, 7.
<https://www.xcmg-ukraine.com.ua>
моб. +38 050 447 93 93
моб. +38 067 457 00 44