

XGA3250D5NC G5

ТРЕХОСНЫЙ САМОСВАЛ

HANVAN G5 DUMP TRUCK TECHNICAL SPECIFICATION



UNIVERSAL MACHINERY LLC

XUZHOU XCMG AUTO MANUFACTURING CO., LTD

Основные характеристики

	整机型号/Vehicle Model	XGA3250D5NC		
设计质量参数 Mass parameter	整备质量/Curb weight	15500 kg		
	最大允许总质量//GVW	41500kg		
性能参数 Performances	最高车速/Max. Speed	80 km/h		
	最小转弯直径/ Min. turning diameter	18.6m		
	最大爬坡度/Grade ability (≥)	28%		
	最大驻坡度/Hill-hold ability (≥)	20%		
	油箱容积/Fuel Tank	300L		
尺寸参数 Dimensions	外形尺寸 Overall dimensions	长/Length	8580mm	
		宽/Width	2550mm	
		高/Height	3600mm	
		轴距/Wheelbase (mm)	3800+1400	
	轮距/Wheel tread	前轮/Front	2005mm	
		后轮/Rear	1860mm	
		最小离地间隙/Min. Clearance	260mm	
		接近角/Approach angle	25°	
		离去角/Departure angle	23°	
		前悬/Front suspension	1485mm	
		后悬/Rear suspension	1795mm	
		货箱尺寸 Cargo size	5600mm×2350mm×1500mm	
驾驶室/Cab	型号/Model	汉风/G5LM		
	乘员人数/Passengers	2, 3		
发动机/Engine	型号/Model	D10.38-50		
	总排量/Displacement	9.726L		
	额定功率/Output power	276kW		
	最大扭矩/torque/speed	1560 N.m		
离合器/Clutch	型号/Model	Φ430 推式膜片弹簧离合器 Pull type diaphragm spring clutch		
	操纵方式/Operation	液压操纵气助力/Hydraulic manual		
变速器 /Transmission	型号/Model	10JSD160		
	操纵方式/Operation	软操/Flexible shaft		

	前进档速比/Forward ratio		14.86-1.00
	倒档速比/Reverse ratio		14.24、3.19
驱动桥/Driven axle	型号/Model		16T MAN
	主减速器速比/Ratio		5.262
	制动器类型/Brake type		鼓式/Drum type
	差速锁/Differential lock		轴间、轮间差速锁 Differential lock between axles and wheels
前轴/Front axle	型号/Model		9.5T
	制动器类型/Brake type		鼓式/Drum type
车轮 Wheel	轮辋/Rim		8.50V-20
	轮胎/Tire		12.00R20-18PR
车架/Frame	型式/Type		等宽直通梁/Rectangular beam
	主纵梁截面/Main beam(mm)		300×90×8
	衬梁截面/Auxiliary beam(mm)		284×80×8
	车架总成宽度 Width of chassis structure		865mm
悬架 Suspension	前/Front	型式/Type	纵置多片簧/Multi-spring
		钢板弹簧片数 Amount of spring plate	10
	后/Rear	型式/Type	纵置多片簧/Multi-spring
		钢板弹簧片数 Amount of spring plate	13
转向系 Steering	转向器型式/Steering type		Φ120/循环球式液压助力 Circulating ball type hydraulic power
	转向器速比/Ratio		23.27
	转向油泵最大压力 Max pressure of pump		14Mpa
制动系 Brake	额定工作压力/Rated working pressure		1Mpa
	行车制动系型式/Driving brake		双回路气压制动 Dual circuit pneumatic braking
	驻车制动系型式/Parking brake		弹簧储能断气制动 Spring energy storage air brake
	辅助制动系型式/Assistant brake		发动机排气制动 Engine exhaust brake
	电压/Voltage		24V
	发电机功率/Generator power		1.96 kW
	蓄电池电压/电容 Battery voltage and Capacitance		2×12V/165Ah





ООО «Юниверсал Машинери»
г. Киев, Бульвар Верховного Совета, 7.
<https://www.xcmg-ukraine.com.ua>
моб. +38 095 457 00 44
моб. +38 067 457 00 44
e-mail: info@xcmg-ukraine.com.ua